

### SMOOTH BORE PTFE HOSE WITH RUBBER COVER

#### APPLICATION:

A suction and delivery hose for chemicals, foodstuff and pharmaceutical industry. Resistant to high temperature. The hose is produced with high quality elastomers, with excellent chemical and mechanical properties.

#### CONSTRUCTION:

Smooth PTFE inner core complies with the FDA 21 CFR 177.1550, 177.2600 standards, UPS XXIII class VI and European Pharmacopoeia 3.1.9. Multiple reinforcements of synthetic plies, steel wire and outer cover of Silicone or EPDM which is conductive, abrasion, ageing and ozone resistant.

#### TEMPERATURE RANGE:

-60°C - +250°C. (The operating temperature of the hose is directly dependent upon the specific fluid been conveyed.)



Code	ID	OD	Working Pressure	Burst Pressure	Minimum Bend Radius
	MM	MM	BAR	BAR	MM
SKT10	9.5	16.5	180	550	100
SKT12	12.7	20.6	145	440	110
SKT16	16	24.2	130	400	150
SKT20	19	27.4	80	240	180
SKT25	25.4	38	65	200	250
SKT38	38	52	40	160	475
SKT50	50	64	25	100	650

#### AVAILABLE IN:

- FOOD GRADE
- MILKY WHITE SILICONE COVER OR BLUE EPDM COVER
- VACCUM
- PERMANENTLY ANTI-STATIC